

Declaration of performance No.:1/11/2014/CPR

1. Unique identification code of the product - type

DALMATYŃCZYK fasada EPS S EPS-EN 13163-T(1)-L(2)-W(2)-Sb(5)-P(5)-BS75-DS(N)2-DS(70,-)2-TR80

2. Intended use/es

Thermal insulation for buildings.

3. Manufacturer

Termo Organika[®] Sp. z o.o.

ul. B. Prusa 33, 30-117 Kraków, Poland

4. System/s of AVCP

System 3

5. Harmonised standard:

Harmonised standard: EN 13163:2012

Notified body/ies: ITB - Instytut Techniki Budowlanej (notified body No 1488)

6. Declared performances

Table 1

Essential characteristics	Performance	Declared level / Classe / Limit values/ /NPD ¹⁾	Harmonised technical specifi- cation		
Reaction to fire	Reaction to fire	E			
Continuous Glowing combustion	Continuous Glowing combustion	NPD			
Water permeability	Water permeability	NPD			
Release of dangerous substances to the indoor environment	Release of dangerous substances ²⁾	NPD			
Direct airborne sound insulation index	Dynamic stiffness	NPD			
Acoustic absorption index	-	NPD			
Impact noise transmission index (for flo- ors)	Dynamic stiffness	NPD	EN 13163:2012		
	Thickness, d _L	NPD			
	Compressibility	NPD			
	Thermal resistance R _D	See Table 2			
Thermal resistance	Declared thermal conductivity λ_{D}	0,044 [W/mK]			
	Thickness, d _N	T(1) (±1 mm)			
Water vapour permeability	Water vapour transmission	NPD			
			1. A		

Termo Organika Sp. z o.o.

ul. Bolesława Prusa 33, 30-117 Kraków

tel.: +48 12 427 07 40, fax: +48 12 427 27 21, www.termoorganika.pl, e-mail: styropian@termoorganika.pl

Termo Organika

Declaration of performance No.: 1/11/2014/CPR

	Compressive stress at 10 % deforma- tion	NPD	
Compressive strength	Deformation under specified com- pressive load and temperature condi- tions	NPD	_
Tensile/Flexural strength	Bending strength	BS75 (≥ 75 kPa)	-
	Tensile strength perpendicular to faces	TR80 (≥ 80 kPa)	
Durability of reaction to fire against he- at,weathering, ageing/degradation	Durability characteristicsc 3)	E	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance R _D ⁴⁾	See Table 2	-
	Declared thermal conductivity $\lambda_{\text{D}}^{4)}$	0,044 [W/mK]	EN 13103.2012
	Durability characteristics	NPD	1
Durability of compressive strength against ageing and degradation	Compressive creep	NPD	-
	Freeze-thaw resistance	NPD	-
	Long term thickness reduction	NPD	

¹⁾ No performance determined ²⁾ European test methods are under development ³⁾ The fire performance of EPS does not deteriorate with time ⁴⁾ Thermal conductivity and thermal resistance of EPS products do not change with time.

According to Article 6, paragraph 5 of the Regulation of the European Parliament and of the Council (UE) No 305/11one informs that the information required by Regulation No 1907/2006 of The European Parliament and of The Council of 18 December 2006 concerning registration, evaluation, authorisation and applied restriction of chemicals (REACH) are given in " the Product information" which is on the manufacturer's website www.termoorganika.pl

Additional information in form of instructions and technical data sheets are available on the manufacturer's website www.termoorganika.pl

Table 2 Declared thermal resistance is dependent upon the thickness of a product.

Thickness d _N , [mm]	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Thermal resistance R _D , [m ² K/W]	0,20	0,45	0,65	0,90	1,10	1,35	1,55	1,80	2,00	2,25	2,50	2,70	2,95	3,15	3,40
Thickness d _N , [mm]	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300
Thermal resistance R _D , [m ² K/W]	3,60	3,85	4,05	4,30	4,55	4,75	5,00	5,20	5,45	5,65	5,90	6,10	6,35	6,55	6,80

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jerzy Pasternak, Plenipotentiary of the Board for FPC

in Kraków, 06.11.2014

Jerry Naternah

Note: This is the translation of the Declaration of Performance issued originally in Polish

Termo Organika Sp. z o.o. ul. Bolesława Prusa 33, 30-117 Kraków tel.: +48 12 427 07 40, fax: +48 12 427 27 21, www.termoorganika.pl, e-mail: styropian@termoorganika.pl