

## Declaration of performance No.:5/11/2014/CPR

### 1. Unique identification code of the product - type

GOLD fasada EPS S      EPS-EN 13163-T(1)-L(2)-W(2)-Sb(2)-P(5)-BS100-DS(N)2-DS(70,-)2-TR100

### 2. Intended use/es

Thermal insulation for buildings.

### 3. Manufacturer

Termo Organika® Sp. z o.o.

ul. B. Prusa 33, 30-117 Kraków, Poland

### 4. System/s of AVCP

System 3

### 5. Harmonised standard:

Harmonised standard: EN 13163:2012

Notified body/ies: ITB – Instytut Techniki Budowlanej (notified body No 1488)

### 6. Declared performances

Table 1

Essential characteristics	Performance	Declared level / Classe / Limit values/ /NPD <sup>1)</sup>	Harmonised technical specification
<b>Reaction to fire</b>	Reaction to fire	E	EN 13163:2012
<b>Continuous Glowing combustion</b>	Continuous Glowing combustion	NPD	
<b>Water permeability</b>	Water permeability	NPD	
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances <sup>2)</sup>	NPD	
<b>Direct airborne sound insulation index</b>	Dynamic stiffness	NPD	
<b>Acoustic absorption index</b>	-	NPD	
<b>Impact noise transmission index (for floors)</b>	Dynamic stiffness	NPD	
	Thickness, d <sub>L</sub>	NPD	
	Compressibility	NPD	
<b>Thermal resistance</b>	Thermal resistance R <sub>D</sub>	See Table 2	
	Declared thermal conductivity λ <sub>D</sub>	0,038 [W/mK]	
	Thickness, d <sub>N</sub>	T(1) (±1 mm)	
<b>Water vapour permeability</b>	Water vapour transmission	NPD	

<b>Compressive strength</b>	Compressive stress at 10 % deformation	NPD	EN13163:2012	
	Deformation under specified compressive load and temperature conditions	NPD		
<b>Tensile/Flexural strength</b>	Bending strength	BS100 ( $\geq 100$ kPa)	EN13163:2012	
	Tensile strength perpendicular to faces	TR100 ( $\geq 100$ kPa)		
<b>Durability of reaction to fire against heat, weathering, ageing/degradation</b>	Durability characteristics <sup>3)</sup>		E	
<b>Durability of thermal resistance against heat, weathering, ageing/degradation</b>	Thermal resistance $R_D$ <sup>4)</sup>	See Table 2	EN13163:2012	
	Declared thermal conductivity $\lambda_D$ <sup>4)</sup>	0,038 [W/mK]		
	Durability characteristics	NPD		
<b>Durability of compressive strength against ageing and degradation</b>	Compressive creep	NPD	EN13163:2012	
	Freeze-thaw resistance	NPD		
	Long term thickness reduction	NPD		
<sup>1)</sup> No performance determined <sup>2)</sup> European test methods are under development <sup>3)</sup> The fire performance of EPS does not deteriorate with time <sup>4)</sup> Thermal conductivity and thermal resistance of EPS products do not change with time.				
According to Article 6, paragraph 5 of the Regulation of the European Parliament and of the Council (UE) No 305/2011 one informs that the information required by Regulation No 1907/2006 of The European Parliament and of The Council of 18 December 2006 concerning registration, evaluation, authorisation and applied restriction of chemicals (REACH) are given in "the Product information" which is on the manufacturer's website <a href="http://www.termoorganika.pl">www.termoorganika.pl</a>				
Additional information in form of instructions and technical data sheets are available on the manufacturer's website <a href="http://www.termoorganika.pl">www.termoorganika.pl</a>				

Table 2 Declared thermal resistance is dependent upon the thickness of a product.

Thickness $d_N$ , [mm]	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Thermal resistance $R_D$ , [ $m^2K/W$ ]	0,25	0,50	0,75	1,05	1,30	1,55	1,80	2,10	2,35	2,60	2,85	3,15	3,40	3,65	3,90
Thickness $d_N$ , [mm]	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300
Thermal resistance $R_D$ , [ $m^2K/W$ ]	4,20	4,45	4,70	5,00	5,25	5,50	5,75	6,05	6,30	6,55	6,80	7,10	7,35	7,60	7,85

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jerzy Pasternak, Plenipotentiary of the Board for FPC

in Kraków, 06.11.2014

Note: This is the translation of the Declaration of Performance issued originally in Polish